

19" DYNAmic Basic Free Standing Cabinets

Width: 600 mm. Depth: 800 mm.

Width=600mm Depth=800mm

Standard Heights:

4 different U heights: 22U,26U 32U, 42U

Standards, and Compliances:



ISO 9001:2008

Quality Management System

EN 61587 -1:2012 Mechanical Structures for Electronic Equipment

IEC 297-1, 19" mounting IEC 297-2 Overall cabinet dimentions



CE conform to

EN 60950-1:2006 Information Technology Equipment – Safety – Part-1-General Requirements



Environment Friendly;

- *ISO 14001 Environmental Management System
- *Environmental awareness
- *RoHS compliancy
- *% 100 Recyclable Material.

Load Capacity: 600 kgs.

DYNAmic series Networking Enclosures, with 19" w:600mm and d:800mm physical sizes, with max internal usable depth and 4 different height, gives a wide selection chart for users.

Standard Colors:




RAL 9005 Black

RAL 7035 Light Grey



19" DYNAmic Basic Cabinets


W:600mm D:800mm Drawings



BOTTOM VIEW




FRONT VIEW



SIDE VIEW



REAR VIEW




TOP VIEW




19" DYNAmic Basic Cabinets W:600mm D:800mm Drawings







ISOMETRIC VIEW

EXPLODED VIEW





MAX / STD / MIN EQUIPMENT MOUNTING DISTANCE



DIMENSIONS IN WIDTH AND HEIGHT

| DYNAmic Basic Series Free Standing 19" Cabinets W=600mm D=800mm | | | | | | | | | | | | | |
|---|---|------------------|-------------|----------|---|---------------------|-----------------------|---------------------|---|-----------------|---|------------------------------------|---------------------------------|
| ROOT Product Number *** | Product Description | Size WXDXH mm | HU size (U) | HU in mm | *H mm, overall without feet and/or castor | Width Overall mm | Width Rail to Rail | Depth Overall mm | **Depth Shipping Conf. Rail to Rail mm | QTY IN PACK AGE | ASSEMBLED PACKAGE DIMENTIONS WXDXH | Standard NET Weight of product kgs | Gross Weight of Products kgs |
| LN-DB22U6080-CC | 22U 19" Free Standing Cabinet W=600mm D=800mm | 600x800x1125 | 22U | 978 | 1125 | 600 | 19" | 800 | 570 | 1 | 680x880x1265 | 43 | 52 |
| LN-DB26U6080-CC | 26U 19" Free Standing Cabinet W=600mm D=800mm | 600x800x1300 | 26U | 1155 | 1300 | 600 | 19" | 800 | 570 | 1 | 680x880x1440 | 51 | 60 |
| LN-DB32U6080-CC | 32U 19" Free Standing Cabinet W=600mm D=800mm | 600x800x1560 | 32U | 1422 | 1560 | 600 | 19" | 800 | 570 | 1 | 680x880x1700 | 63 | 72 |
| LN-DB42U6080-CC | 42U 19" Free Standing Cabinet W=600mm D=800mm | 600x800x2010 | 42U | 1867 | 2010 | 600 | 19" | 800 | 570 | 1 | 680x880x2150 | 82 | 93 |

^{*} Please add 30mm to H mm once used with Leveling Feet, add 80mm to H mm once used with castor set. ** See min and max Adjustable depth variations on drawings.

^{***} CC= LG for Light Grey RAL 7035 & BL for Black RAL 9005 for customers to define while ordering.

 $^{****} Unless defined delivery is in Flat Pack, Please add A notation to The Part number for assembled delivery ie.\ LN-DB22U6080-CC-A to the Part number for assembled delivery in the Part number fo$

^{*****} The Logistical information provided in above chart is based on assembled product since packing details of flat-pack is changing based on transport vehicle and the delivery location. Please consider delivery notes, packing lists and recent data provided with the logistics services of Lande.